

Dell Pro 34 Plus USB-C Hub Monitor P3425WE(DELL-P3425WE)

Dell Pro 34 Plus USB-C Hub Monitor P3425WE - LED monitor - curved - 34.1" - 3440 x 1440 UWQHD @ 100 Hz - IPS - 350 cd/m² - 1500:1 - 5 ms - HDMI, DisplayPort, USB-C - BTO - with 3 years Basic Hardware Service with Advanced Exchange after remote diagnosis



The Dell Pro 34 Plus USB-C Hub Monitor P3425WE offers an immersive viewing experience with its expansive 34.1-inch diagonal, UWQHD resolution of 3440 x 1440. This monitor is designed to enhance productivity, featuring a variety of built-in devices such as a KVM switch and a USB 3.2 Gen 1/USB-C hub, providing seamless connectivity for multiple devices. The anti-glare display with flicker-free technology ensures comfort during long working hours, while the LED edgelight system and 3-sided bezel-less design create an aesthetically pleasing workspace.

This monitor is engineered for versatility with height, swivel, and tilt adjustments, allowing users to achieve the perfect viewing angle. The Dell ComfortView Plus feature reduces harmful blue light emissions, enhancing eye comfort and providing a friendly experience for users. With impressive color support, the Dell Pro monitor displays 1.07 billion colors, making it suitable for tasks that require color accuracy and precision. The 90 watts USB Power Delivery ensures that connected devices are efficiently powered, minimizing cable clutter and streamlining the workspace.

Key Selling Points

- 34.1-inch UWQHD display provides expansive viewing
- Built-in KVM switch facilitates easy device management
- USB Power Delivery of 90 watts reduces cable clutter
- ComfortView Plus technology enhances eye comfort
- Versatile adjustments for customized viewing angles

Product Features

Impressive resolution

The 3440 x 1440 pixel resolution allows for sharp and detailed images, enhancing clarity in visuals and work presentations.

Ergonomic design

Features such as height, swivel, and tilt adjustments enable users to customize the screen position for maximum comfort and productivity.

Broad connectivity options

Equipped with HDMI, DisplayPort, and USB-C interfaces, this monitor supports various connection types to ensure compatibility with numerous devices.

Enhanced color performance

With a color gamut of 99% sRGB, this monitor delivers accurate colors for tasks that require precise color representation.

Environmentally friendly

Certified with EPEAT Gold and ENERGY STAR, this monitor is designed with sustainability in mind, reducing environmental impact.

Main Specifications

Product Description	Dell Pro 34 Plus USB-C Hub Monitor P3425WE - LED monitor - curved - 34.1"
Device Type	LED-backlit LCD monitor - 34.1"
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/2141837
Energy Class	Class F
Power Consumption (On mode)	28.7 W
Curved Screen	Yes
Features	USB 3.2 Gen 1/USB-C hub, KVM Switch, USB PD 90 Watt
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	UWQHD 3440 x 1440 at 100 Hz
Pixel Pitch	0.2325 mm
Brightness	350 cd/m ²

Contrast Ratio	1500:1
Response Time	5 ms (fast), 8 ms (normal)
Colour Support	1.07 billion colours
Colour Gamut	99% sRGB (CIE 1931)
Input Connectors	HDMI, DisplayPort, USB-C
Built-in Ethernet	Yes
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand (highest position)	81.595 cm x 22.942 cm x 54.125 cm
Weight	9.91 kg
Pricing Type	BTO
Environmental Standards	ENERGY STAR Qualified EPEAT Gold
Compliant Standards	Plug and Play, RoHS, BFR-free, PVC-free, TCO Certified Edge, TCO Certified 10.0, DisplayPort 1.4, HDCP 1.4, TUV Rheinland Eye Comfort Certification (4-star)
Bundled Services	3 years Basic Hardware Service with Advanced Exchange after remote diagnosis

Extended Specification

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/2141837
Energy Class	Class F
Diagonal Size	34.1"
Curved Screen	Yes (3800R)
Built-in Devices	USB 3.2 Gen 1/USB-C hub, KVM Switch
USB Power Delivery	90 Watt
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	UWQHD 3440 x 1440 at 100 Hz
Pixel Pitch	0.2325 mm
Pixel Per Inch	110
Brightness	350 cd/m ²
Contrast Ratio	1500:1
Colour Support	1.07 billion colours
Colour Gamut	99% sRGB (CIE 1931)
Response Time	5 ms (fast), 8 ms (normal)
Vertical Refresh Rate	30 - 100 Hz
Horizontal Refresh Rate	28 - 151 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	Wide Viewing Angle, 3-sided bezelless, Dell ComfortView Plus, Low Blue Light technology, flicker-free panel, LED edgelight system, Mercury free, Dell Easy Arrange, arsenic-free glass, picture by picture, picture in picture
Dimensions (WxDxH)	81.595 cm x 22.942 cm x 54.125 cm - with stand (highest position)
Weight	9.91 kg

Manufacturer Warranty

Bundled Services	3 years Basic Hardware Service with Advanced Exchange after remote diagnosis
------------------	--

Miscellaneous

Features	Security lock slot (cable lock sold separately), VESA interface support, integrated cable management
Included Accessories	Cable tie
Cables Included	1 x DisplayPort 1.4 cable - DisplayPort to DisplayPort - 1.8 m 1 x USB-C 3.2 Gen 1 cable - USB-C - 1.8 m 1 x USB 3.2 Gen 1 cable - USB Type A to B - 1.8 m
Compliant Standards	Plug and Play, RoHS, BFR-free, PVC-free, TCO Certified Edge, TCO Certified 10.0, DisplayPort 1.4, HDCP 1.4, TUV Rheinland Eye Comfort Certification (4-star)
Pricing Type	BTO
Security Slot Type	Kensington security slot

Power

Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	28.7 W
Power Consumption SDR (On mode)	29 kWh/1000h
Power Consumption (Typical)	27.6 Watt
Power Consumption (Max)	200 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.3 Watt

Software / System Requirements

Included Software	Dell Display Manager
-------------------	----------------------

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

Connectivity

Interfaces	DisplayPort 1.4 (HDCP 1.4) HDMI (HDCP 1.4) USB-C upstream/DisplayPort 1.4 Alt Mode with Power Delivery (power up to 90W) USB-B 3.2 Gen 1 upstream USB-C 3.2 downstream with Power Charging (power up to 15W) 3 x USB 3.2 Gen 1 downstream LAN (RJ-45)
------------	---

Dimensions & Weight

Dimensions & Weight Details	With stand (lowest position) - width: 81.595 cm - depth: 22.942 cm - height: 39.125 cm - weight: 9.91 kg With stand (highest position) - width: 81.595 cm - depth: 22.942 cm - height: 54.125 cm - weight: 9.91 kg Without stand - width: 81.595 cm - depth: 8.298 cm - height: 35.8 cm - weight: 6.9 kg
-----------------------------	--

Dimensions & Weight (Shipping)

Shipping Weight	14.36 kg
-----------------	----------

Mechanical

Display Position Adjustments	Height, swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	60
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm

Sustainability Information

EPEAT Compliant	EPEAT Gold
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0

What's in the box

Dell Pro 34 Plus USB-C Hub Monitor P3425WE
DisplayPort 1.4 cable - 1.8 m
USB-C 3.2 Gen 1 cable - 1.8 m
USB 3.2 Gen 1 cable - 1.8 m
Cable tie
Software

*TD SYNEX is not responsible for errors in the documentation of products.