

## Lenovo Preferred Pro II(4X30M86882)

### Lenovo Preferred Pro II - Keyboard - USB - AZERTY - Belgium French - black

The Preferred Pro II USB keyboard is very similar to those that come as standard with ThinkCenter desktop systems. It is also compatible with USB enabled ThinkStation and ThinkPad notebook systems and docks.



## Key Selling Points

- Rubberized wrist rest coating provides soft support surface for your comfort
- Three operation mode LEDs located on right upper corner will be activated individually
- The three indicators have the nomenclature 'Num Lock', 'Caps Lock' and 'Scroll Lock'
- All the keys in QWERTY and NUMPAD sections are rubber dome switch keys
- Adjustable tilt legs

## Product Features

### Enhanced compatibility

Designed to seamlessly integrate with PC systems, this keyboard offers a Plug-and-Play experience for a hassle-free setup.

### Reliable connectivity

With its wired USB interface, this keyboard ensures a stable and uninterrupted connection during critical use, eliminating the worries of battery life or wireless interference.

## Main Specifications

Product Description	Lenovo Preferred Pro II - keyboard - AZERTY - Belgium French - black Input Device
Device Type	Keyboard
Interface	USB
Connectivity Technology	Wired
Localization and Layout	AZERTY Belgium French
Hot Keys Function	Caps Lock
Numeric Keypad	Yes
Colour	Black
Dimensions (WxDxH)	45.33 cm x 16.88 cm x 3.416 cm
Weight	850 g
Manufacturer Warranty	1-year warranty

## Extended Specification

### General

Device Type	Keyboard
-------------	----------

Interface	USB
Hot Keys Function	Caps Lock
Localization and Layout	AZERTY Belgium French
Keyboard Technology	Rubber dome
Adjustable Height	Yes
Features	Numeric keypad
Width	45.33 cm
Depth	16.88 cm
Height	3.416 cm
Weight	850 g

#### **Manufacturer Warranty**

Service & Support	Limited warranty - replacement - 1 year
-------------------	---

#### **Miscellaneous**

Colour	Black
Compliant Standards	VCCI, BSMI, CB, IC, FCC, KCC, EAC, RCM

#### **Environmental Parameters**

Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	8 - 80%

\*TD SYNEX is not responsible for errors in the documentation of products.